



ADT Always There®

Camera Quick Reference Guide

Category	540 TVL Cameras				PTZ Camera	D/N IR Bullet Cameras		
MODEL NUMBER	A-CC540TDN	A-CK540HB	A-CF540 A-CF540DNIR A-CF540DNIRB	A-CV540 A-CV540DNIR	A-CC10PTZK	S35CHPS/ S35CHPS36	S35CH S35CH36RJ	SDN655/ SDN655PS
DESCRIPTION	Full Body Camera	Env. Hsg Camera / Heater/Blower	Fixed Dome	Fixed Vandal Dome	10X PTZ mini vandal dome	Day/Night	Day/Night	True Day/Night
RESOLUTION	540 TVL	540 TVL	540 TVL	540 TVL	430 TVL	550 TVL	550 TVL	550 TVL
IMAGE SENSOR	1/3"	1/3"	1/3"	1/3"	1/4"	1/3"	1/3"	1/3"
LENS	3.3-8mm	5-60mm DC AI	4-9mm DC AI	4-9mm DC AI	3.15-31.5mm	6mm / 3.6mm	6mm	3.8-9.5mm VF AI
IR LEDS	-	-	23 IR LEDES (82~98 ft. range)	23 IR LEDES (82~98 ft. range)	-	6 (30 ft. beam)	6 (30 ft. beam)	18 (50 ft. beam)
POWER SOURCE	24VAC / 12VDC RJ-11	24VAC / 12VDC RJ-11	24VAC / 12VDC RJ-11	24VAC / 12VDC RJ-11	24VDC via RJ-11 12VDC / 24VAC via 2-wire	12VDC	RJ-11	12VDC / RJ-11
FEATURES / OTHER	TRUE Day/Night	(2) 100' power/video cables included	Pendant/wall mount available	Pendant/wall mount available	IP66 Rated for outdoor use	Includes 12VDC PS & mounting bracket	Includes mounting bracket	Includes 12VDC PS & mounting bracket

Category	RJ-11 Dome	Fixed Dome Camera	Miniature Bullet Cameras		Covert Cameras, Tower Cam and Mullion Cam			
MODEL NUMBER	A-DS1B	FD375VA	A-S230CWX	S230CWPS	CTH36PB	A-CC54PIR	CC48HS / FS100H / FS150H	MC52028B / S / Z
DESCRIPTION	B&W Motorized PT Camera	Fixed Dome	Color	Color	TowerCam (black)	PIR Housing	Day/Night Covert Height, Mini Strip	MullionCam (black, silver, bronze)
RESOLUTION	380 TVL	480 TVL	380 TVL	380 TVL	520 TVL	540 TVL	525 TVL	520 TVL
IMAGE SENSOR	1/3"	1/3"	1/3"	1/3"	1/3"	1/3"	1/3"	1/3"
LENS	3.6mm	4-9mm DC AI	3.6mm	3.6mm	3.6mm	5.5mm	3.7mm	2.8mm
POWER SOURCE	RJ-11	24VAC / 12VDC	RJ-11	12VDC	12VDC	RJ-11	RJ-11 / 12VDC	12VDC
FEATURES / OTHER	Low Cost	Pendant/wall mount available	Includes mounting bracket	Includes 12VDC PS & mounting bracket	Includes 12VDC PS, optional adapter A-RJ2BNCST for RJ-11	Includes mounting bracket	FS100H / FS150H includes 12VDC PS	Includes 12VDC PS, optional adapter 1512AC for RJ-11



877-433-6766 / www.ADT-Matrix.com

Ik110309

INTERNET
CONNECTION
POWERED BY **2dvr.com**



ADT Always There®

DVR Quick Reference Guide



MODEL NUMBER	A-SDR402E-250	A-SDR415E	A-ADT800E / A-ADT1600E	A-XDP8E / A-XDP16E
Video Compression	H.263 (subset of MPEG4)	H.263 (subset of MPEG4)	H.263 (subset of MPEG4) (ASP)	H.263 (subset of MPEG4) (ASP)
Display / Record Speed	120 ips	120 ips	120 ips	240 ips
File Size (KB)	2/4/8/12 (x2 for 2CIF)(x4 for 4CIF)	2/4/8/12 (x2 for 2CIF)(x4 for 4CIF)	2/4/8/12 (x2 for 2CIF)	2/4/8/12 (x2 for 2CIF)(x4 for 4CIF)
Video Inputs	4 (looping)	4 (looping)	8, 16 (looping)	8, 16 (looping)
Standard HDD Sizes	250GB (1-slot)	250GB / 500GB (2-slots)	250GB / 500GB / 1TB / up to 3TB	250GB / 500GB / 1TB / up to 3TB
MONITOR OUTPUTS				
VGA	Yes	Yes	Yes	Yes
SVHS	No	No	No	Yes
Composite	Yes	Yes	Yes	Yes
Spot monitor	No	No	Yes (1)	Yes (4)
Record Resolution	336 x 224 / 672 x 224 / 672 x 448	336 x 224 / 672 x 224 / 672 x 448	336 x 224 / 672 x 224	352x240/704x240/704x480
Audio Inputs/Outputs	4/1	4/1	2/1	4/1
Archive Media	External USB-IDE HDD; CD-RW or flash drive for clip copy back up	Internal DVD-RW & External USB-IDE HDD; CD-RW or flash drive for clip copy back up	Internal CD-RW External USB-IDE HDD; CD-RW or flash drive for clip copy back up	Internal DVD-RW & External USB-IDE HDD; CD-RW or flash drive for clip copy back up or scheduled archiving also SCSI port for archiving
AUXILIARY INPUTS & OUTPUTS				
USB / SCSI Port	Yes (1)-v2.0 / No / No	Yes (2)-v2.0 / No / No	Yes (2)-v2.0 / No	Yes (3)-v2.0 / Yes (Ultra-wide, 68-pin)
# Remote Connections	2-admin, 10-watch, 2-search	2-admin, 10-watch, 2-search	2-admin, 10-watch, 2-search	2-admin, 10-watch, 2-search
Mouse Support	Yes	Yes	Yes	Yes (included)
IR Remote Control Port	Yes (included)	No	No	Yes (included)
10 / 100 Base T RAS+ / IE	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
Accessories	A-XDLBW2 lock box	A-XDLBW2 lock box	A-XDLBW2 lock box	A-XDLBW2 lock box



ADT Always There®

Monitor Quick Reference Guide

Category	LCD		PVM				CRT	
MODEL NUMBER	M170CP2/ M170CP2D M190CP2 / M190CP2D	ML757 / ML970W ML2200W	M201P-WDR	M200LC3/ M201LC3-WDR	M260WLC / M261WLC-WDR	M320WLC / M321WLC-WDR	NM201A-WDR / NM321W-WDR	A-MC1574FN
DESCRIPTION	17" / 19" LCD	17" / 19"W / 22"W	20.1" LCD with WDR camera	20.1" LCD Panel no-camera / WDR	26" Wide LCD Panel no-camera / WDR	32" Wide LCD Panel no-camera / WDR	20" / 32" Network LCD with WDR Camera	15" Color Flat Screen CRT
RESOLUTION	1280 x 1024	1280 x 1024 / 1440 x 900 1680 x 1050	1600 x 1200	1600 x 1200	1366 x 768	1366 x 768	1600 x 1200 1366 x 768	500 TVL
AUDIO	-	-	Stereo	Stereo	Stereo	Stereo	Stereo	2-ch
CAMERA LENS	-	-	2.8~11mm VF, AI	2.8~11 VF, AI-DC	2.8~11mm VF, AI-DC	2.8~11mm VF, AI-DC	2.8-11mm VF, AI	-
POWER SOURCE	120VAC - 12VDC	120VAC - 12VDC	120VAC - 12VDC	12VDC	24VDC	24VDC	12VDC / 120VAC	120VAC
FEATURES	Narrow bezel, desk stand included	Low Cost VGA Only	2-video input, looping video motion detection	WDR Camera	WDR Camera	WDR Camera	80GB HDD EMB, Advertising	640 x 480 / 1366 x 768
ACCESSORIES	Wall/Ceiling/Rack Mount available	Wall/Ceiling Mount available	Wall/Ceiling/Rack Mount available	Wall/Ceiling Mount available	Wall/Ceiling Mount available	Wall/Ceiling Mount available	CSW778CW Mount	A-BM1415 Wall/ Ceiling Mount



877-433-6766 / www.ADT-Matrix.com

INTERNET CONNECTION
POWERED BY 2dvr.com